



# PS1

## Single Gas Monitor



Actual size.



### Features

- On/Off capability
- Field adjustable alarm settings
- Single gas monitors for H<sub>2</sub>S, O<sub>2</sub>, CO, SO<sub>2</sub>
- Easy one button operation
- Displays real time value
- Datalogging as standard
- Includes fully programmable menu for alarms and latching/non-latching settings
- Alarms: Audible, visual, vibrating, TWA, STEL, low battery and end of life
- Rugged stainless steel alligator clip
- 2 year warranty

### Bump Test & Calibration Station

- Fast visual indication
- Simple bump test or calibration
- Full data and calibration results

### Detection, Protection, Innovation



**GMI. CONFIDENCE WHERE SAFETY IS CRITICAL.** Gas Measurement Instruments designs, manufactures and markets a wide range of the highest quality proven personal portable and fixed gas monitoring systems. GMI is an international brand with a worldwide network of distributors and dedicated service centers ensuring fast and effective turnaround on instrument calibration and repair. Our uncompromising engineering excellence, established in over half a century of leadership, enables us to meet the exacting demands of industries where safety is critical. By building and maintaining strong relationships with our customers, GMI understands the unique challenges of the diverse markets we serve. Today, our proud heritage of pioneering gas leak monitors and detectors is shaping the future of GMI.





The PS1 monitors a single gas, for a variety of applications. Widely used in the oil and gas industry, this rugged, extremely lightweight and accurate monitor clips easily onto a collar or vest. This puts the instrument near the breathing zone for maximum user protection and safety. Audible, visual, and vibrating alarms alert the user, should gas be present and alarms can be latching until the user acknowledges that an alarm is present.

The PS1 Bump Test and Calibration Station is designed to give a fast visual indication that instruments are calibrated correctly. Just place the instrument in the cradle and close the lid. Calibration is complete in 90 seconds and bump testing in 60 seconds. Results can be easily extracted for Calibration Certificate printing at your convenience.

Manual bump testing and calibration is also possible and only requires a cylinder of test gas and regulator. A manual calibration can be performed in less than two minutes with results stored on the PS1.

PS1 TECHNICAL SPECIFICATIONS	
<b>Size:</b>	85 (H) x 55 (W) x 29 (D) mm 3.4" (H) x 2.2" (W) x 1.16" (D)
<b>Weight:</b>	86g (3.0 oz)
<b>Temp. Limits:</b>	-20° to + 50° C (-4° to +122° F)
<b>Humidity:</b>	0-98% RH (non-condensing)
<b>Alarms:</b>	Visual 360° Light bar Vibrating Audible 95 dB User programmable, includes TWA, STEL
<b>Display:</b>	LCD backlit display
<b>Battery:</b>	Lithium
<b>Enclosure:</b>	High impact ABS poly blend
<b>Rating:</b>	IP67 (Dust-tight and waterproof to 1m)
<b>Approvals:</b>	IECEX: Ex ia IIC T4 Ga ATEX Ex II 1G Ex ia IIC T4 Ga UL913: Class I, Div 1, Groups A, B, C, D, T4 MED 96/98/EC As amended CE Class I, Div 1, Groups A, B, C, D T4
<b>Outputs:</b>	Optical IR
<b>Datalogging:</b>	1 minute logging for 24hrs then over-writing 10 calibration logs, 50 bump test logs, ON/OFF session logs
<b>Warranty:</b>	2 years

## Applications

<b>Petrochemical</b>	<b>Pulp and Paper</b>	<b>Chemical</b>
<b>Forklift Operations</b>	<b>Off-Shore</b>	<b>Cities &amp; Municipalities</b>
<b>Fire Departments</b>	<b>Gas and Oil</b>	<b>Boiler Room Monitoring</b>

ACCESSORIES	
<b>63450</b>	Auto bump & calibration station

PART #	GAS TYPE	RANGE	RESOLUTION	TYPE	LIFE	ALARM 1	ALARM 2	STEL	TWA
<b>63324</b>	H <sub>2</sub> S	0-100 ppm	1 ppm	Electrochemical	2 yrs	10 ppm	20 ppm	10 ppm	5 ppm
<b>62403</b>								20 ppm	10 ppm
<b>63002</b>	O <sub>2</sub>	0-25%	0.1%	Electrochemical	2 yrs	19.5%	23.5%	N/A	N/A
<b>63424</b>	CO	0-500 ppm	1 ppm	Electrochemical	2 yrs	30 ppm	200 ppm	200 ppm	30 ppm
<b>62404</b>						35 ppm	50 ppm		35 ppm
<b>63524</b>	SO <sub>2</sub>	0-20 ppm	0.1 ppm	Electrochemical	2 yrs	Disabled	1.0 ppm	1.0 ppm	1.0 ppm
<b>62405</b>						Disabled	5.0 ppm	5.0 ppm	5.0 ppm



Gas Measurement Instruments Ltd

**GMI Headquarters**  
Inchinnan Business Park  
Renfrew  
PA4 9RG  
Scotland  
Tel: +44 (0) 141 812 3211  
Fax: +44 (0) 141 812 7820  
sales@gmiuk.com  
www.gmiuk.com

**Service and Calibration - UK**  
25 Cochran Close  
Crownhill  
Milton Keynes  
MK8 0AJ  
Tel: +44 (0) 1908 568 867  
Fax: +44 (0) 1908 261 056  
service@gmiuk.com  
www.gmiuk.com



**Service and Sales - USA**  
4055 Technology Forest Blvd  
The Woodlands, TX 77381  
Tel: (713) 559-9290  
Toll free: (877) 421-5315  
Fax: (281) 292-2860  
sales@detcon.com  
www.detcon.com

©2013 Gas Measurement Instruments Ltd.  
PS1 (US) product brochure Part No. 99336  
Issue 3 – November 2013

**Distributed by:**